

Women's tops and pants. Pullover tops have side hemline slits. View A has stand-up collar with zipper and facing. View B has optional appliqué and contrast front and back. Views B and C have V-neckline with neckband. Pull-on pants have three lengths, elastic in casing at waist, and optional side seam pockets.



WOMEN'S PANTS & TOPS DESIGNED FOR STRETCH KNITS ONLY
Sizes: 1X-2X-3X-4X Suggested Fabrics: Sweatshirt fleece, French terry, double knit, heavy single knit

| Size | 1X | 2X | 3X | 4X | |
|---|--|--|--|--|----------------------------|
| Finished Length of Top at Cen | ter Back | | | | |
| View A, B & C | 28 1/2 (72) | 29 1/2 (75) | 30 1/2 (77) | 31 1/2 (80) | " (cm) |
| Finished Inside Leg Seam | | | | | |
| View A | 29" (73 cm) – All | Sizes | | | |
| View B | 23" (58 cm) – All | Sizes | | | |
| View C | 6 1/2" (16 cm) – All Sizes | | | | |
| Material Required: Fabric requi | rement allows for nan one | e-way design or shad | ing Extra fabric ma | v be needed to match | design or for shrinkag |
| | | - way acoigii oi siiaa | mg. Dana labite ma | y be necucu to mater | design of for similinag |
| Fabric 60" (152 cm) Wide | rement anows for map, on | c-way design of shad | ing. Datra labric ma | y be needed to mater | design of for similikag |
| | 3 7/8 (3.55) | 4 (3.70) | 4 5/8 (4.25) | 4 3/4 (4.35) | yd (m) |
| Fabric 60" (152 cm) Wide | • | , , | | | 9 |
| Fabric 60" (152 cm) Wide View A | 3 7/8 (3.55) | 4 (3.70) | 4 5/8 (4.25) | 4 3/4 (4.35) | yd (m) |
| Fabric 60" (152 cm) Wide View A View B Fabric | 3 7/8 (3.55) 2 5/8 (2.40) | 4 (3.70) 2 3/4 (2.55) | 4 5/8 (4.25) 3 (2.75) | 4 3/4 (4.35) 3 1/8 (2.85) | yd (m) yd (m) |
| Fabric 60" (152 cm) Wide View A View B Fabric Contrast | 3 7/8 (3.55) 2 5/8 (2.40) 1 (0.95) 2 3/4 (2.55) | 4 (3.70) 2 3/4 (2.55) 1 1/8 (1.05) | 4 5/8 (4.25) 3 (2.75) 2 1/8 (1.95) | 4 3/4 (4.35) 3 1/8 (2.85) 2 1/8 (1.95) | yd (m) yd (m) yd (m) |
| Fabric 60" (152 cm) Wide View A View B Fabric Contrast View C | 3 7/8 (3.55) 2 5/8 (2.40) 1 (0.95) 2 3/4 (2.55) | 4 (3.70) 2 3/4 (2.55) 1 1/8 (1.05) | 4 5/8 (4.25) 3 (2.75) 2 1/8 (1.95) | 4 3/4 (4.35) 3 1/8 (2.85) 2 1/8 (1.95) | yd (m) yd (m) yd (m) |